RAIDEN INDUSTRIES

+44 7838 374931 info@raidenelectric.co.uk

15 Shardlow Road, Wigston Leicester LE18 1DY

www.raidenelectric.co.uk

STAINLESS STEEL LOCK BALL TIES

Standard and Characteristic

Stainless steel cable technical feature brought to pitch accord with :"Electric equipment of boat".No.of IEC92,totally "is it mould with GB1113-85 metal cable is it bring to pitch to make"and "steel seagoing vessel enter magnitude and build norm"relevant regulation.Pitch and take the normal environment temperature of condition of work-25 degrees Centigrade-160 degrees Centigrade ≥500N of pulling force,body material ICr18Ni9.Suitable for tying up the cable in the internal and external places of the room,such as in the open,humidity,high temperature,etc.,wear resistance corrosion resistance radiation resistance,fire protection.

Material: **S316**

Specification	Mini Loop Tensile		Specification	Mini Loop Tensile	
	lbs	Kg		lbs	Kg
4.6x127	135	60	10x150	225	100
4.6x152			10x200		
4.6x200			10x250		
4.6x300			10x300		
4.6x350			10x350		
4.6x400			10x400		
4.6x450			10x500		
4.6x500			10x550		
4.6x550			10x600		
4.6x600			10x650		
4.6x650			10x700		
4.6x700			10x750		
4.6x750			10x800		
4.6x800			10x850		
			10x900		
			10x950		
			10x1000		
			10x1050		
			10x1100		
7.9x150	180	80	12x200	270	120
7.9x200			12x250		
7.9x250			12x300		
7.9x300			12x350		
7.9x350			12x400		
7.9x400			12x500		
7.9x500			12x550		
7.9x550			12x600		
7.9x600			12x650		
7.9x650			12x700		
7.9x700			12x750		
7.9x750			12x800		
7.9x800			12x850		
7.9x850			12x900		
7.9x900			12x950		
7.9x950			12x1000		
7.9x1000			12x1050		
7.9x1050			12x1100		
7.9x1100			12x1200		

UL LISTED (POSITIONING DEVICE) 41XT. E225994